

**Date/Doc revision:** 16-Mar-2023

**Project Name:** Panic Pendant

#### TECHNICAL SPECIFICATIONS

- **Model:** XPP01
- **Tamper:** N/A
- **LED:** x1
- **Button:** x1
- **Wired:** N/A
- **Case Material:** PC+ABS
- **Screws:** x4 PB1.7 x 5mm
- **Color:** White
- **Mounting:** Wristband, Belt clip
- **Battery:** CR2032 3.0V (225mAh) x1
- **Battery Life:** ≈ 7 years @ 30 triggers per day
- **Standby Current:** 0.9 uA
- **Active Current:** 2.4 mA
- **Operating Temperature:** 32° to 120.2°F (0° to 49°C)
- **Relative Humidity (Storage):** 80% Max. non-condensing
- **Weather Proofing:** IPX7
- **Regulatory:** FCC 2AVDCXPP01-E-1433



#### CONNECTIVITY

- **Transmitter Frequency:** 433MHz
- **Wireless Signal Range:** up to 492 ft.\*, open air, with Security Panel\*\*
- **Modulation:** OOK
- **Encryption:** Yes, 1-way
- **Frequency Hopping:** N/A
- **Supervision:** N/A

#### DIMENSIONS

- **Height:** 1.65 in.
- **Width:** 1.45 in.
- **Depth:** 0.43 in.

#### FEATURES

- **Actions:** Medical, Police, Mode Set at The XP02 Panel

\* The front of the Sensor is facing the panel LCD. The panel is installed at a height of 4.92 ft. The Sensor is installed at a height of 4.59 to 4.92 ft.

\*\* The location of the Sensor can have a significant effect on range. In open/unobstructed situations, the transmitter range may be greater. In adverse wireless conditions, you may encounter a decrease in range.